



ALPINE DISTRIBUTION

HIGH TENSILE STEEL STRAPPING

High Tensile strapping is manufactured from cold rolled steel and heat treated to provide high tensile strength and ductility. High tensile strength affords extra protection and shock resistance under all strap-

Width	Gauge	Avg. Break		Elongation	Coil Wind	Available Finish
		Strength	Feet/lbs			
1/2"	.020	1450	29.41	5-12%	OSC.	Black (Z)
5/8"	.020	1960	21.79	5-12%	OSC.	Black (Z, J)
5/8"	.023	2250	18.94	5-12%	OSC.	Black
3/4"	.020	2175	19.61	5-12%	OSC.	Black
3/4"	.022	2395	17.83	5-12%	OSC.	Black
3/4"	.025	2720	15.69	5-12%	OSC.	Black (B,Z)
3/4"	.029	3160	13.52	5-12%	OSC.	Black
3/4"	.029	3160	13.52	6.5-12%	R/W	Black
3/4"	.031	3375	12.65	5-12%	OSC.	Black
1 1/4"	.025	4530	9.41	5-12%	R/W	Black Black
1 1/4"	.029	5260	8.11	5-12%	R/W	(Z,B,U,J) Black
1 1/4"	.029	4200	8.11	5-12%	R/W	Punched
1 1/4"	.031	5620	7.59	6.5-12%	R/W	Black (J)
1 1/4"	.035	6350	6.72	6.5-12%	R/W	Black (B)
1 1/4"	.044	7975	5.35	6.5-12%	R/W	Black (J)
2"	.044	12760	3.34	6.5-12%	R/W	Black

Coil ID for all material is 16" AAR-11 Embossed
Available in Z=Zinc B=Blue U=Unptd J=Jumbo

Contact: Linda Gibson (Linda@alpinecw.com) 503-254-8395
Contact: Randy Stout (RandyS@alpinecw.com) 541-345-0386