

MANUAL PLASTIC TENSIONERS AND SEALERS

Slotted drum tensioners provide maximum tension and cut after sealing. These tensioners are built for rugged applications but are simple to use. A low cost alternative to combination tools.

Front action sealers are used with handles perpendicular to width of strapping. Operator pushes handles together to close seal.

Model	Width (in)	Gauge	Strap Type
 ORS 1100.19	3/8" - 384"	015-.050	PP/PET
 ORS 1300.40	5/8" - 1 1/4"	.023 - .060	PP/PET/Cord



ORS 1100.19

3/8" - 384"

015-.050

PP/PET



ORS 1300.40

5/8" - 1 1/4"



.023 - .060

PP/PET/Cord

Contact: Linda Gibson (Linda@alpinecw.com) 503-254-8395

Contact: Randy Stout (RandyS@alpinecw.com) 541-345-0386

MANUAL PLASTIC TENSIONERS AND SEALERS

	Model	Width (in)	Gauge	Strap Type
	ORS 1400.19	3/8" - 3/4"	.0150-0.035	PP
	ORZ 3200.13	1/2"	.015-.028	PET
	ORZ 3200.16	5/8"	.015-.025	PET
	ORZ 3210.16	5/8"	.028-.040	PET
	ORZ 3300.13	1/2"	.015-.023	PP
	ORZ 3410.13	1/2"	.025-.040	PP
	ORZ 3410.16	5/8"	.025-.040	PP

Contact: Linda Gibson (Linda@alpinecw.com) 503-254-8395
 Contact: Randy Stout (RandyS@alpinecw.com) 541-345-0386