



PNEUMATIC PLASTIC COMBINATION TOOLS

Pneumatic tensioners allow the operator to effectively tighten the plastic strapping around your package. Uniform tension is maintained on each strap with clean, regulated and lubricated air pressure. Dependable tool performance is a function of the filter-regulator-lubricator, which is recommended with any pneumatic tool.

With an Alpine manual plastic combination tool you can tension, seal, and shear strapping in a single operation. By eliminating the need for separate single-function tools, combination tools make your strapping application faster, more convenient and more efficient.






Model	Width (in)	Gauge (in)	Tension (lbs)	Max Psi.	Strap
P355	1/2"	.026 - .041	470	87lbs.	PET
P355	5/8"	.025 - .041	470	87lbs.	PET
P356	5/8"	.025 - .041	880	93lbs.	PET
P356	3/4"	.040 - .053	880	93lbs.	PET

Contact: Linda Gibson (Linda@alpinecw.com) 503-254-8395
 Contact: Randy Stout (RandyS@alpinecw.com) 541-345-0386



ALPINE DISTRIBUTION

PNEUMATIC PLASTIC COMBINATION TOOLS

	Model	Width (in)	Gauge (in)	Strap
	OR-4000.13	1/2"	.015 - .028	PP/PET
	OR-4000.16	5/8"	.020 - .040	PP/PET
	OR 4500.13	1/2"	.020 - .031	PP/PET
	P403	1/2"	.016 - .035	PP/PET
	P404	5/8"	.020 - .035	PP/PET

Contact: Linda Gibson (Linda@alpinecw.com) 503-254-8395
Contact: Randy Stout (RandyS@alpinecw.com) 541-345-0386