



## SYSTEMS

Strapex's plastic strapping machines combine overall durability with practicality, creating a line of plastic strapping machines designed to perform efficiently and reliably in all production capacities. Suitable for a variety of applications, the SMG is available in different models to accommodate a wide range of package sizes and configurations.

### **Operator Friendly-**

SMG strapping machines are built with features that make it easier to operate than other strapping machines. Mobile and ready to use anywhere, the SMG features adjustable working heights for integration into multiple lines. Other features include simple coil changing, push button tension adjustments and easy troubleshooting.

### **Easy To Maintain**

SMG strapping machines simplify maintenance by combining a lubrication free design with fewer moving parts. All parts are easily accessible and routine maintenance can be performed without tools.

### **Reduces Downtime**

SMG strapping machines are equipped with several built-in features to help reduce downtime. The system automatically attempts to re-feed the strap up to three times if a strap jam occurs. A loop ejector prevents trap from jamming if the machine cycles without a package in place. And when the strap coil is near the end, the machine automatically ejects the last piece of strap, eliminating the need for operator retrieval.

### **Cost Efficient Strapping**

The SMG 10 strapping machine can utilize 5mm polypropylene thin strap, while providing the same degree of package performance and reliability as 3/8" or 1/2" strap. With 5mm thin strap, customers get more strap per coil, fewer coil changeovers and better overall strap tension.

Contact: Linda Gibson (Linda@alpinecw.com) 503-254-8395

Contact: Randy Stout (RandyS@alpinecw.com) 541-345-0386



# SYSTEMS

## Systems

	SMG10	SMG15	SMG20s	SMG25	SMG25s	SMG50	SMG55	SMG65	SMG65i	SMG75i
Min Pkg Width	4"	4"	2.25"	4"	2.25"	4"	4"	N/A	N/A	
Max Pkg Wt (lbs)	77	77	77	77	110	77	77	77	110	110
Cycles Per Min	70	65	70	60	60	70	65	65	65	65
Strap Tension (lbs), Up to	65	100	67	100	100	67	100	135	135	135
Weight (lbs)	375	375	375	420	375	529	529	419	375	419
Working Height	26-33"	26-33"		26-33"		28-37"	28-37"	22-40"	22-42"	22-42"

### Arch Size

20x16 (in.)	X		X		X					
25x20 (in.)	X	X		X		X	X	X	X	X
33x25 (in.)				X		X	X			
33x33 (in.)				X			X	X		
33x49 (in.)								X		
33x61 (in.)								X		
49x20 (in.)				X						
49x33 (in.)				X						
61x20 (in.)				X						

Contact: Linda Gibson ([Linda@alpinecw.com](mailto:Linda@alpinecw.com)) 503-254-8395  
 Contact: Randy Stout ([RandyS@alpinecw.com](mailto:RandyS@alpinecw.com)) 541-345-0386